



2009 MOTORCYCLES
ROCKER™ C





The perfect machine for riders looking to leave a real impression on what seems like endless streets of chopper sameness.

MODEL FEATURES

ENGINE

Rigid-Mounted Twin Cam 96B™ Engine

Black powder-coated, rigid-mounted Twin Cam 96B™ engine with chrome covers packs a punch with loads of torque (117Nm/86 ft. lbs. at 3200 rpm).

FRONT FENDER

Sport Front Fender

Sport front fender with color matched brace supports.

HANDLEBARS

Stainless Steel, Pull-Back Handlebars

Custom adjustable, internally wired V-bars place the rider in a laid-back chopper-style position.

SEAT

2-in-1 Convertible Trick™ Seat

This 2-in-1 convertible Trick™ seat hides the comfortable passenger seat when cruising solo.

EXHAUST

Chrome, Staggered Shorty Exhaust

Chrome, staggered shorty exhaust system with dual mufflers.

REAR FENDER

Low Profile Rear Fender

It defies physics, as it appears to float above the rear wheel, that's because all the hardware is hidden.

REAR TIRE

Fat 240mm Rear Tire

Ultra fat and controlling, this hot rod will grip the road.

HEADLAMP

Chrome, Bullet Headlamp

This polished chrome bullet headlamp projects a bright beam of light down any dark street.

OIL TANK

"Horseshoe" Style Oil Tank

Color-matched, cast aluminum finned "horseshoe" oil tank with chrome external oil lines.

CONSOLE

Chrome, Stretch Low-Profile Console

Stretch low profile with integrated speedo.

RISER

Chrome, V-Bar Riser

Two-piece, sculpted polished chrome 5-inch V-curved riser.

FUEL TANK

5.0-Gallon Fuel Tank

Custom stretched 5.0-gallon fuel tank.



SPECIFICATIONS

DIMENSIONS	U.S. UNITS
Length	95.0 in.
Seat Height	
Laden ¹	25.2 in.
Unladen	27.4 in.
Ground Clearance	5.10 in.
Rake Steering Head/Trail	36.0° / 6.20 in.
Wheelbase	69.2 in.
Fuel Capacity	5.0 gal.
Oil Capacity	3.5 qt.
Weight	
Dry Weight	686.3 lbs.
Running Order	720.6 lbs.

POWERTRAIN	
Engine ²	Air-cooled, Twin Cam 96B™
Displacement	96.00 cu. in.
Bore x Stroke	3.75 in. x 4.38 in.
Engine Torque ³	87.90 ft lbs @ 2750 rpm
Fuel System ⁴	Electronic Sequential Port Fuel Injection (ESPFI)
Compression Ratio	9.2:1
Miles Per Gallon ⁵	
ESPFI	54 hwy / 35 city
Primary Drive	Chain, 34/46 ratio
Gear Ratio (overall)	
1st	9.312
2nd	6.421
3rd	4.774
4th	3.926
5th	3.279
6th	2.790

**WHEELS/TIRES****Wheels ⁶**

Front	Polished, 5-Spoke Cast Aluminum
Rear	Polished, 5-Spoke Cast Aluminum
Wheel Option	N/A

Tire Size

Front	90/90-R19 52H
Rear	240/40-R18 79V

ELECTRICAL**Instruments**

Tank-mounted electronic speedometer with odometer, time-of-day clock on odometer, dual tripmeter, fuel gauge with low fuel warning light and countdown feature, low oil pressure indicator light, engine diagnostics readout, LED indicator lights, 6-speed indicator light

Indicator Lamps ⁷

High beam, neutral, low oil pressure, turn signals, engine diagnostics, security system (optional), 6-speed, low fuel warnings.

Reverse Function

N/A

CHASSIS**Brakes**

4-piston front and 2-piston rear

Parking Brake

N/A

Lean Angle (per SAEJ1168)


29.5° / 32.5°

Exhaust System

Chrome, staggered shorty exhaust w/ dual mufflers




COLOR OPTIONS



Vivid Black



Flame Blue Pearl



Crimson Red
Sunglo

--	--	--	--	--	--

PRICING[®]

MSRP

Vivid Black	\$ 19,499
Color	\$ 19,844
Twotone	N/A
Custom Color	N/A
Anodized	N/A
Wheel Option	N/A
Chrome Engine Covers Option	N/A
Security System Option	\$ 345
California Emissions	\$ 200
Freight	\$ 330
ABS	N/A
Cruise Control	N/A



1. Measurement reflects 180 lb./81.7 kg operator weight.
2. Recommended 91 octane or higher fuel (R+M)/2.
3. Values shown are nominal. Performance varies by country and region.
4. Standard and optional fuel systems may vary by country.
5. Estimated from fuel economy tests on a sample motorcycle from the corresponding family conducted by HarleyDavidson under ideal laboratory conditions. Not all motorcycle models undergo fuel economy testing. Fuel economy and mileage may vary among motorcycle models within a family. Your mileage may vary depending on your personal riding habits, weather conditions, trip length, vehicle condition and vehicle configuration and other conditions. Break-in mileage may vary.
6. Standard and optional wheels may vary by country and region.
7. North America security system includes immobilizer; outside North America the security system includes immobilizer and siren.
8. Prices listed are the Manufacturer's Suggested Retail Prices. Options such as color are available at additional cost. Prices exclude dealer setup, taxes, title and licensing and are subject to change. Dealer prices may vary.

Vehicles depicted may differ from vehicles manufactured and delivered. Specifications and prices listed may differ from specifications and prices of vehicles manufactured and delivered.

All product descriptions (including depictions, specifications, dimensions, measurements, ratings and competitive comparisons) are based on available information at the time of publication. Although such descriptions are believed correct, errors and changes can occur and complete accuracy cannot be guaranteed.

Harley-Davidson may make changes at any time to prices and specifications, and may change or discontinue models, without notice and without incurring any obligation.

Attention: Vehicles in the configurations shown and many of the accessories described in this catalog may not be available for sale or use in some locations. Please check with your dealer for complete product details and the latest information.

All models feature 6-speed transmission (VRSC™ models and Sportster® models are 5-speed) and carbon fiber belt final drive; multi-plate clutch with diaphragm spring in oil bath; and 2-year unlimited mileage warranty.

